

COMCAT™ AS

Complete Bio Catalyst

BIO CATALYST WASTEWATER TREATMENT

- COMCAT™ AS is formulated to increase bio degradation of organic materials in industrial, pulp and paper, food processing, petrochemical and municipal wastewaters.
- COMCAT™ AS improves the dissolved oxygen transfer rates in aerobic environments lowering energy costs.
- COMCAT™ AS enhances anaerobic biogas generation in anaerobic digesters.
- COMCAT™ AS speeds degradation of complex organic compounds by severing molecular bonds allowing microbiology to more easily consume the smaller molecular particles.

FOR BEST RESULTS:

- Do not store below 45°F or above 105°F.
- DO NOT FREEZE.
- Use within 24 months of arrival date.

KEEP OUT OF REACH OF CHILDREN.
DO NOT TAKE INTERNALLY.

APPLICATION

Suggested
Minimum Dose

Suggested
Maximum Dose

Normal / Maintenance

0.5 ppm

10 ppm

Upset

5 ppm

20 ppm

Used in conjunction with Bio Energizer® typically at a 1:1 ratio. Contact your local PROBIOTIC SOLUTIONS® Representative for optimal use conditions and any questions.

STORAGE AND DISPOSAL:

Keep product in original container. Do not transfer into food or drink containers. Triple rinse when empty for recycling. Always dispose of container in accordance with local, state and/or federal regulations.

CONDITIONS OF SALE:

The information contained on this label is believed to be accurate and reliable. Buyer and user acknowledge and assume all liability resulting from the use of this material. Follow directions carefully. Timing, method of application, weather, and other factors are beyond the control of the seller.

8.34 lb per gallon @ 68° F.
1.00 kg per liter @ 20° C.
pH 3.0 - 3.5

30 Gallons • Net Wt. 250.2 lbs.
113.56 liters • Net Wt. 113.56 kg



**Probiotic
SOLUTIONS®**

Trademarks of and Produced by
BIO HUMA NETICS, INC. © 2005-2020
1331 W. Houston Ave., Gilbert, AZ 85233 • 480.961.1220

www.probiotic.com

PS-980-08152019